

**COLD****COOLING CABINETS • KÜHLSCHRÄNKE • ARMOIRES FRIGORIFIQUES
FRIGORÍFICOS • FRIGORÍFICOS**

Form	Model	Dim. cm	Capacity/ Refrigerant	Temp °C	Version	Power		€
						Watt	Volt	
	TTKPR14L	60·60·85	180 lt. Gas R600a	+2° +10°C	- Injected polyurethane insulation HCFC/CFC FREE - White anti-corrosion treated steel sheet cabinet and tank, (AISI 430 stainless steel cabinet, AISI 304 stainless steel tank on the "PRX" model) - Solid door - Four adjustable feet - Thermometer - Lock - Hermetic compressor with protection - Static condensing system	100	220-240/1N	820,-
	TTKPRX14L	60·61,5·83	141 lt. Gas R600a	+1° +15°C		100	220-240/1N	1.190,-
								
	CHEF600PX	67·86,4·195	Gas R404a	+2 +10° C	- Injected polyurethane insulation HCFC/CFC FREE - AISI 430 stainless steel cabinet - AISI 304 stainless steel tank - Capacity 600 lt. 5x GN 2/1 - Solid door with magnetic gasket (upon request: left hand opening door) - Lock - Four unidirectional rollers and two adjustable feet - Thermometer - Hermetic compressor with protection	400	230/1N	2.570,-
								
	CHEF600NX	67·86,4·195	Gas R404a	-18° -25° C	- Injected polyurethane insulation HCFC/CFC FREE - AISI 430 stainless steel cabinet - AISI 304 stainless steel tank - Capacity 600 lt. 5x GN 2/1 - Solid door with magnetic gasket (upon request: left hand opening door) - Four unidirectional rollers and two adjustable feet - Thermometer - Hermetic compressor with protection - Fan assisted condensing system	470	230/1N	2.630,-
								
	KICPR60	77,5·73·186,5	Gas R134a Ventilated	+3° +8° C		240	230/1N	1.550,-
	KICN60	77,5·73·186,5	Gas R404a Static	-18° -25° C	- Injected polyurethane insulation HCFC/CFC FREE - AISI 430 stainless steel cabinet on the "X" models, and white anti-corrosion treated steel sheet on the other models - Capacity 640 lt. 5x GN 2/1 - Food safe plastic tank - Solid door with magnetic gasket (upon request: left hand opening door)	360	230/1N	1.750,-
	KICPRX60	77,5·73·186,5	Gas R134a Ventilated	+3° +8° C	- Lock - Two adjustable feet - Digital thermometer - Mechanical adjustment with automatic defrosting - Hermetic compressor with protection	240	230/1N	1.790,-
	BMB0019	77,5·73·186,5	Gas R404a Static	-18° -25° C		360	230/1N	1.990,-
								

COOLING CABINETS

CHEF 600 PX

- Injected polyurethane insulation HCFC/CFC FREE
- AISI 430 stainless steel cabinet on the "X" models, and white anti-corrosion treated steel sheet on the other models
- AISI 304 stainless steel tank on the "X" models, and white anti-corrosion treated steel sheet on the other models
- Solid door with magnetic gasket (upon request: left hand opening door)
- Lock - Four unidirectional rollers and two adjustable feet
- Thermometer - Hermetic compressor with protection

CHEF 600 NX

- Injected polyurethane insulation HCFC/CFC FREE
- AISI 430 stainless steel cabinet on the "X" models, in white anti-corrosion treated steel sheet on the other models
- AISI 304 stainless steel tank on the "X" models, in white anti-corrosion treated steel sheet on the other models
- Solid door with magnetic gasket (upon request: left hand opening door)
- Lock - Four unidirectional rollers and two adjustable feet
- Thermometer - Hermetic compressor with protection
- Fan assisted condensing system

CHEF 600 PX

- Isolamento in poliuretano iniettato SENZA HCFC/CFC
- Mobile in lamiera d'acciaio inox AISI 430 nei modelli "X", in lamiera d'acciaio bianca, trattata anti-corrosione negli altri modelli
- Vasca in lamiera d'acciaio inox AISI 304 nei modelli "X", in lamiera d'acciaio bianca, trattata anti-corrosione negli altri modelli
- Porta cieca con guarnizione magnetica (in opzione: porta con apertura a sinistra)
- Serratura a chiave - Quattro rullini e due piedini regolabili
- Termometro
- Compressore ermetico con protettore
- Sistema condensante con ventilatore

CHEF 600 NX

- Mobile in lamiera d'acciaio inox AISI 430 nei modelli "X", in lamiera d'acciaio bianca, trattata anticorrosione negli altri modelli
- Vasca in lamiera d'acciaio inox AISI 304 nei modelli "X", in lamiera d'acciaio bianca, trattata anti-corrosione negli altri modelli
- Porta cieca con guarnizione magnetica (in opzione: porta con apertura a sinistra)
- Serratura a chiave - Quattro rullini e due piedini regolabili
- Termometro - Compressore ermetico con protettore



- Injected polyurethane insulation HCFC/CFC FREE
- AISI 430 stainless steel cabinet on the "X" models, and white anti-corrosion treated steel sheet on the other models
- Food safe plastic tank
- Solid door with magnetic gasket (upon request: left hand opening door)
- Lock - Two adjustable feet
- Digital thermometer
- Mechanical adjustment with automatic defrosting
- Hermetic compressor with protection
- Static condensing system (fan assisted)

- Isolamento in poliuretano iniettato SENZA HCFC/CFC
- Mobile in lamiera d'acciaio inox
- AISI 430 nei modelli "X", in lamiera d'acciaio bianca, trattata anti-corrosione negli altri modelli
- Vasca termoformata in plastica a norme alimentari
- Porta cieca con guarnizione magnetica (in opzione: porta con apertura a sinistra)
- Chiusura a chiave
- Due piedini regolabili
- Termometro a cristalli liquidi
- Regolazione meccanica con sbrinamento automatico
- Compressore ermetico con protettore
- Sistema condensante statico a fili (con agitatore)

